DEPARTMENT OF REGISTRATION AND EDUCATION BONALD E. STACKLER DIRECTOR, SPRINGFIELD

NATURAL RESOURCES

RONALD E. STACKLER..... CHAIRMAN
BIOLOGY THOMAS PARK
CHEMISTRY M. S. GUTOWSKY
ENGINEERING ... ROBERT H. ANDERSON
FORESTRY CHARLES E. OLMSTED
GEOLOGY LAURENCE L. SLOSS
SOUTHERN ILLINOIS UNIVERSITY
ELBERT H. HADLEY
UNIVERSITY OF ILLINOIS

WILLIAM L. EVERITT

Illinois State Water Survey

WATER RESOURCES BUILDING • MAIL: BOX 232, URBANA, ILLINOIS 61801 • AREA CODE 217
805 E. SPRINGFIELD, CHAMPAIGN PHONE 333-2210

WILLIAM C. ACKERMANN, CHIEF

April 8, 1975

REPORT ON GROUNDWATER CONDITIONS
IN SECTION 4, T. 44N., R. 2E.,
WINNEBAGO COUNTY, ILLINOIS
By

EPA Region 5 Records Ctr.

James P. Gibb, Assistant Engineer

This report on the availability of groundwater for a supplemental municipal supply for the City of Loves Park in Section 4, T. 44N., R. 2E., Winnebago County, is prepared at the request of Loves Park Water Department, 5440 Walker Avenue, Loves Park, Illinois 61111.

The enclosed data on the municipal wells at Rockford, North Park, and Loves Park generally describe the groundwater conditions in the area of interest. West of the location of interest along the Rock River and over a preglacial bedrock valley extensive sand and gravel deposits are tapped as a source for municipal and industrial supplies. However, as indicated in the attached geologic report, the area of interest lies on a bedrock upland and only limited quantities of water (less than 15 or 20 gpm) can generally be developed from the sand and gravel deposits present in this area.

The existing Loves Park Well No. 3 taps the St. Peter, Ironton-Galesville, and Eau Claire Sandstones at a depth of 863 feet (bottom elevation near sea level). The reported yield of this well is from 800 to 1000 gpm.

The mineral quality of water from this well is illustrated on the enclosed analysis (see Lab. No. 03726). The water is hard, contains little or no iron, and is only moderately mineralized (300 to 350 mg/l total dissolved minerals).

Larger quantities of water (from 1000 to 2500 gpm) have been developed by several wells tapping the St. Peter, Ironton-Galesville, Eau Claire, and underlying Mt. Simon Sandstones. Wells tapping these units range in depth from about 1200 to 1600 feet and are generally finished near elevations 450 to 500 feet below mean sea level.

Water obtained from these wells is only slightly more mineralized than that obtained from the shallower bedrock units. Hardness ranges

from 300 to 350 mg/l, iron 0.1 to 1.0 mg/l, and total dissolved minerals from 350 to 400 mg/l.

In summary, the chances for developing the desired supply at the location of interest appear good. One well penetrating into the Eau Claire rocks at depths from about 800 to 900 feet should be capable of yielding from 500 to 750 gpm. If a larger quantity of water is desired, a well penetrating into the underlying Mt. Simon rocks at a depth of 1300 to 1350 feet should be capable of yielding from 1000 to 2000 gpm.

esi A. Simor

ILLINOIS ENVIRONMENTAL PROTECTION AGENCY

DIVISION OF PUBLIC WATER SUPPLIES

Inventory Sheet

Date inventoried 1/11/74


Supply: LOVES PARK

10.01(2)(間1/2)(2)(2)(2)(2)(部1間1四1(2)(2)(2)(2)(2)(2)(3)(图1(

Sheet 1 of 23

Item:

LOCATION



14.11- gues look 2.4

State Water Survey Division





Water Resources Building 605 East Springfield Avenue P.O. Box 5050, Station A Champaign, Illinois 61820 217/333-2211 Illinois Department of Energy and Natural Resources

May 8, 1984

Mr. Dennis P. McKenna
Executive Director
Winnebago County Soil and Water Conservation District
3820 Auburn St.
Rockford, Illinois 61103

Dear Mr. McKenna:

The Water Use Act of 1983 has required the Illinois State Water Survey to evaluate the potential impacts of proposed wells designed to pump 100,000 gallons per day (70 gallons per minute) or more. You have submitted to us information on the Loves Park Well #4 formation on the Loves Park Well #4 formation on Winnebago County. The well has a design capacity of 2000 gpm, is 1313 feet deep, and is completed in the Cambrian-Ordovician aquifer.

Well records of the area indicate that overlying the Cambrian-Ordovician aquifer are the Shallow Dolomite aquifer and an unconsolidated sand and gravel aquifer. Our records indicate that within a half mile radius of Well #4 there are numerous wells finished in the Shallow Dolomite and sand and gravel aquifers. Also, the closest well finished in the same aquifer is Loves Park Well #3

Based on our evaluation of the available data we conclude that the wells finished in the overlying Shallow Dolcmite or sand and gravel aquifer should not be affected by Loves Park Well #4. Furthermore, the Loves Park Well #3 finished in the same aquifer as that of Well #4 will exhibit approximately 16 to 69 feet of additional drawdown as a result of well interference by Well #4. The exact amount will depend on how Well #4 is to be used. These amounts were determined from distance-drawdown curves for the Loves Park Well #4 pumping at the design capacity for 3 days and 365 days. Although the well may not be pumped at the 2000 gpm design rate or the selected time period, the data was used because it yields a range of minimum and maximum estimates of the impact of Loves Park Well #4. The well interference represents 6.8 to 29 percent of the present total available drawdown and was considered as having a minimum to moderate impact on Loves Park Well #3 because of the large amount of total available drawdown for wells completed in the Cambrian-Ordovician aquifer.

Larnan Larnan

At present the available groundwater resource is able to meet the anticipated water demand of the Loves Park Well #4. Aquifer yield data suggests that future withdrawals may be inhibited because the present withdrawals are fast approaching the safe yield of the aquifer. Therefore, the potential for growth could be limited.

Should you have any questions or comments, please feel free to contact us.

Sincerely, ILLINOIS STATE WATER SURVEY

Mark W. Hampton Assistant Hydrologist Phone: (217) 333-1724

MWH:bh

MIN . Kr. 1 ... 7 .. 4

State Water Survey Division





Water Resources Building 605 East Springfield Avenue P.O. Box 5050, Station A Champaign, Illinois 61820-9050 217/333-2211 Illinois Department of Energy and Natural Resources

Northern Regional Office 101 North Island Avenue Batavia, Illinois 60510 (312) 879-6466

July 6, 1984

Illinois Environmental Protection Agency Division of Public Water Supply 2200 Churchill Road Springfield, Illinois 62706

Gentlemen:

Attached are copies of test data for Well No. 4 at Loves Park, Winnebago County. That data were collected by Milaeger Well and Pump Company.

Very truly yours,
STATE WATER SURVEY DIVISION

Robert T. Sasman Hydrologist

RTS/jm Encl.

Well Production Test

Milaeger Well and Pump Company Loves Park

Winnebago County

WELL NO. 4

Owner:

Loves Park

Location:

WIN, non non responsive

Date of Test:

2/6/84

Length of Test:

22 hours

Aquifer:

Sandstone (Aq Code 6697)

Date Drilled:

February 1984

WELL DATA

Pumped Well

Well No.:

4

Depth:

1313'

Driller:

Milaeger Well and Pump Company

Hole Record:

26" 0 - 370', 214" 370-1313'

Casing Record:

26" +1 to 90', 22" +2 to 370' (cemented)

Screen Record:

_

Gravel Pack Record:

u. –

Pump & Power:

Test turbine

Surface Elevation:

888'

Measuring Point:

top of casing, 2' above LSD

Measuring Equipment:

Water Sample: Static Level:

2001

Remarks:

MILAEGER WELL AND PUMP CO., INC.

LOVES PARK WELL #4
DRILLERS LOG

<u>DEPTHS</u>	<u>DF</u> THICKNESS	RILLERS LOG DESCRIPTION	<u>FORMATION</u>
0-85	85	sand, gravel, clay	glacial drift
85-335	250	limestone	Galena Platte ville Dolomi
335-541	250	sandstone, white-fine	Glenwood-St. Peter Sandst
541-585		sandstone, pink-coarse	
585-610	55	limestone, gray-hard	Trempealeau
610-615		limestone, gray-hard with shale streaks	
615-630		limestone, light brown-hard	
630-640	·	limestone, gray	
640-674	50	sandy limestone, pinkish with red shale streaks	Franconia
675-690		shale, red & gray, muddy & sand	Y
690-707	160	<pre>sandstone, reddish brown, hard, sharp</pre>	Ironton- Galesville sandstone
707-727		sandstone, gray-hard	
727-740		sandstone, off-white, hard	
740-747		sandstone, white-very hard	
747-755		<pre>sandstone, limestone & shale, reddish, hard</pre>	
755-777		sandstone, pinkish, medium hard	l
777-850		sandstone, white-fine soft	
850-895	347	shale, red-gray, hard	Eau Claire Dolomite
895-937		shale, hard, gray	
937-947	·	shale & limestone, very hard, gr	ay
947-963		sandstone & .shale, hard-gray	
995-1069		sandstone, light gray, very has	rđ
1069-1197		sandstone, white, hard	
1197-1265	116	sandstone, gray, very hard	Undifferent-
1265-1303		sandstone, pink, hard	iated Mount Simon sandston
1303-1313		sandstone, pink with shale streaks, hard	

Analyses are to be performed on unfiltered samples. Waltes water Analyses are to be performed on unfiltered samples. Waltes water OF Minagenery is to be determined as pon of exceeding no. of places shown are reported in the lab Curby of ph 4.5. comments section.

20yanide is to be reported as free gyanide

tests requested but not run oncolorated be explained in the la

tormenta se mini.

か

3702-Plain

5694 MAY22

402-11-11.

Analyses are to be performed on unfiltered samples. exceeding no. of places shown are reported in the lab comments section; 'ests requested but not run should also be explained in the lab comments section.

Environmental Protection Agency

Division of Laboratory Se

Chicago, Minois 20612

Address 2121 W. Taylor Street

H.W.

(76)

じじじじし 115 数 ·				
PARAMETERS *			1.74030 n=	
		ARAMETERS Alkolinity	PP	M•
27 31		Ammonia 63 N		
37	\vdash			
<i>31</i> 44	X	Barium Ba (eC)	* I	2 7
44	Y	Bod -5	<u> </u>	
53	一	Boron 3		· X
58	∇			
	₽	Cadmium Cd	112	00 8
64		Calcium Ca	112	3
69	<u> </u>	COD		<u>. X X 4 4 4 1</u>
73	L	Chloride Cl		. <u>E E E E</u>
	V		SM040	_ 3,8 1.
27		Chromium Cr (tot)	0	·o 0
33		Chromium Cr ⁺⁶		
39	1	Copper Cu 0.02.	<u> </u>	04
45	-	Cyanide ² ON		· ×
52	\vdash	[#/loocit		× × ×
56	<u> </u>	Fluoride F		· X_ Y
61	L	Hardness CaCO3		
65	X	Iron Re I.O	5	· 6
70	X	Lead Ft		<u>ه ۵۰۰ و .</u>
	_	LPC	311050	
27	X	Magnesium Mg	35	4
32	X	Manganese MnO.15	<u>+</u> 0	<u>58 % x 1</u>
38	Ļ	Mercury Hg		·
45	K	Nickel Ni	0	6
51	_	Nitrate-nitrite N		
56	L	Oil and Grease	 	. X ∴ X .
60		pH (Units)	<u> </u>	<u> </u>
63	X	Phenolics 0.001	<u>+</u> 0	010
70		Phosphorus P		
76	X	Potassium K	<u>a6</u>	. 9 222
LPCSMO60				
27		R.O.E. (180°C)		.2 2 2.
31		Salenium Se		·
38	X	Silver Ag		0 82 2
44	X	Sodium Na	28	. 4°
49	Γ,	SC (unhos/em)		·X X X X
53		Sulfate SO ₄		. X/ 25/ \
58	X	Zine En 🖟 🎞 🕻	T'\10	. 0% x

 $^{
m l}$ Alkalinity is to be determined as ${
m prop}$ of CaCO3 at pd 4.5.

STATE OF ILL NO

CHEMICAL ANALYSIS FORM				
Key for Determining Type of Monitoring Point				
(S) Surface Water (G) Ground Water	(L) Leadmate X: Special			
(1) Upstream (1) Monitor Well	(1) Flow or (1) Soil			
(2) Mid-site (2) Private well	seep (2) Waste			
(3) Downstream (3) Spring	(2) Fond (2) Waste (3) Collection (3) Other			
(4) Run-off (4) Lysimeter	System			
(5) Impounded (5) Public W S	!!			
·				
Name (Private Well, Stream, Spring,	Impounded Water only.			
$\frac{L - P - C - C - M - O - 1 - O}{(T)} \qquad \text{SITE INV}$	TENTORY 2 0 1 0 1 5 0 1 (16)			
MONITOR POINT 6 1 0 DATE NUMBER (17) (20) COLLECTE	041381			
Winnebago co I	PC REGION			
	(27)			
Loves Park Re	Responsible Party)			
Legal (1); Illegal (2); Indicate One:	Board Order (X)			
Time Collected 11:10 a.m.	able so collect sample (X)			
Stick-up $\underbrace{1.4}_{(\overline{31})}$ ft. Leg	oth to water [5.] ft. om T.O.C.) (34) (36)			
Cample temp. 3 Eackground (X) (40)				
Ground water sampled by (Indicate one	a). (1) Bailing:			
(2) Pumping; (3) Other (Specify)	(41)			
	2 1 00			
Sample Appearance: Sith Silts	1. Diema 100 Ocor			
Collector comments: Remark 1 vs	lum Food Balance TD=1291			
	THE TAST ATTENDED			
hbs a wetweek.				
Ke. Broks	OLPC .			
Collected by	Div. or Company			
	Div. or Company			
Transported by	517. 51 company			
LAB USE ONLY	LPCSMO20			
Lab No. C004993	Lab Comments:			
Date Rec'd 4-14-81	Thougaint angle			
Rec'd by Kicke Time 1:50 a.m.				
Sample temp. acceptable YES NC	(37) $ (46)$			
Sample properly preserved YES NO	PECENIEN			
Date completed Date forwarded MAY 15. 1981	L (47) - 15 to the total to the \$36)			
Date forwarded MAY 13. 1901	115/2 9 117 207			
(Wantetta	$\left(\frac{1}{57}\right)^{-1} = \frac{10}{10}ML + \frac{11}{10}ML + \frac{11}{10$			
Saffryisor Signature	III EDA DIDO			
Name Division of Johanna A	ILL. E.P.A D.I.P.C.			
	Francis UIMIL UP HILISTRADI T			
	Land Andrews			
of Lab 2121 W. Taylor Street Chicago, Illinois 60612	Continue lab (X) IEFA Lab (X) (77)			

*Analyses are to be performed on additional damples. *Value:
exceeding no. of places shown are reported in the lab comments section;
tests requested but not our should also be explained in the lat
comments section.

Scant Section 1				
		VEAMETERS.	pp.4	
	X			
27 31	X	Armonia as N	12 0 X	
37	X	Arcenic As	0 000	
44	X	Farium Ba	1.681	
_ a	X	900 45	_ < 3 : 1	
53	X	Engra B 💮 🕺	1_111	
53	X	Osámium Fi 🔭	0 0 12;	
64	X	Calvium Jar	1186	
64	X		2311:	
73	X	Tuloride II	****	
	 ,	LP.	* *** * * * * * * * * * * * * * * * *	
27	X	Chromium Cr (1211)	0.001	
33	X	Chromium (r*^	0 0 01	
39	X	Comper Co	0 08;	
45	X	Cynnide CM 1	0.0014	
52	<u></u>	[294] [0] [4	* 7 1	
56	X	El airi le F	treferre	
ól	X	dardness in it.		
65	X	Iron Pe	0 -5 \ \	
70	X	Descal PB	0.000	
		· · · · · · · · · · · · · · · · · · ·	061	
27	X	Manysium Mr	35.3	
32 	X	Manganese In	0 391	
38		Menauny Hg	0000	
45		Vickel Ni	6.9xx.	
51	0	Withhelmitrite A	The second second	
56	6	1011 1 11 5 4	9000 187	
60 63	(pH (Units)	2 2 7 x 1 3	
70	Q	Phenolian X Pholonhomis 2	0.00	
75	X	Potassium K	29 / 1	
27	V	-1-11-(14000)	49981	
31		Newenium Ce	0.00+	
, .	X	Cluer Ag	0 0 0	
44	X	Codium Na 🕠	319:	
49	X	CC (runinos/em)	982 111	
53	X	Silfate 302	* 发	
şa	X	(8)	0.1 x x ;	
		[4]	.)	

TAINATELINE Sold of the section of t

R. M.